SAFETY DATA SHEET

K46W151

Section 1. Identification	
---------------------------	--

Product name	: PRO INDUSTRIAL [™] Pre-Catalyzed Waterbased Semi-Gloss Epoxy Extra White
Product code	: K46W151
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of t	ne substance or mixture and uses advised against
Not applicable.	
Manufacturer	: THE SHERWIN-WILLIAMS COMPANY 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	 US / Canada: (216) 566-2917 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year
Product Information Telephone Number	: US / Canada: (800) 524-5979 Mexico: Not Available
Regulatory Information Telephone Number	: US / Canada: (216) 566-2902 Mexico: Not Available
Transportation Emergency Telephone Number	 US / Canada: (800) 424-9300 Mexico: SETIQ 01-800-00-214-00 / (52) 55-5559-1588 24 hours / 365 days a year

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 2 TOXIC TO REPRODUCTION (Unborn child) - Category 2 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2
	Percentage of the mixture consisting of ingredient(s) of unknown oral toxicity: 22.1% Percentage of the mixture consisting of ingredient(s) of unknown dermal toxicity: 22.1% Percentage of the mixture consisting of ingredient(s) of unknown inhalation toxicity: 22. 1%
GHS label elements	
Hazard pictograms	
Signal word	: Warning
Hazard statements	 Suspected of damaging the unborn child. Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure.
Precautionary statements	
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Do not breathe vapor.
Date of issue/Date of revision	• 9/10/2018 Date of provious issue • 7/4/2018 Version • 10.03 1/4

Date of issue/Date	of revision	: 9/10/2018	Date of previous issue	: 7/4/2018	Version	:10.03	1/11
K46W151	PRO INDUSTRIAL™ Pre Extra White	-Catalyzed Wate	rbased Semi-Gloss Epoxy		SHW-85-	NA-GHS-US	

Section 2. Hazards identification

Response	: Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention.
Storage	: Store locked up.
Disposal	 Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. FOR INDUSTRIAL USE ONLY.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of	: Not available.
identification	

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7
2-(2-Methoxyethoxy)-ethanol	≤3	111-77-3

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary firs	t aid measures
Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effect	<u>ts</u>	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	

Date of issue/Date	of revision	:9/10/2018	Date of previous issue	: 7/4/2018	Version	:10.03	2/11
K46W151	PRO INDUSTRIAL™ Pre Extra White	-Catalyzed Wate	rbased Semi-Gloss Epoxy		SHW-85-	NA-GHS-US	

Section 4. First aid measures

Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
<u>Over-exposure signs</u>	/symptoms
Eye contact	: No specific data.
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations

Individual of an individual of the	and a definition and openial a datafient needed an interesting
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	g : None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide metal oxide/oxides
Special protective actions for fire-fighters	 Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
	inadequate. Put on appropriate personal protective equipment.

	Date of issue/Date	of revision	: 9/10/2018	Date of previous issue	: 7/4/2018	Version : 10.03	3/11
K46W151 PRO INDUSTRIAL [™] Pre-Catalyzed Waterbased Semi-Gloss Epoxy Extra White			SHW-85-NA-GHS-US				

Section 6. Accidental release measures

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non- emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning upSmall spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up
if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and
place in an appropriate waste disposal container. Dispose of via a licensed waste
disposal contractor.Large spill: Stop leak if without risk. Move containers from spill area. Approach release from
upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash
spillages into an effluent treatment plant or proceed as follows. Contain and collect
spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or
diatomaceous earth and place in container for disposal according to local regulations
(see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated
absorbent material may pose the same hazard as the spilled product. Note: see
Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling	g	
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	Exposure limits
Titanium Dioxide	ACGIH TLV (United States, 3/2017). TWA: 10 mg/m ³ 8 hours.
2-(2-Methoxyethoxy)-ethanol	OSHA PEL (United States, 6/2016). TWA: 15 mg/m ³ 8 hours. Form: Total dust None.

Occupational exposure limits (Canada)

Date of issue/Date	of revision	: 9/10/2018	Date of previous issue	: 7/4/2018	Version : 10.03	4/11
K46W151	PRO INDUSTRIAL™ Pre Extra White	e-Catalyzed Wate	erbased Semi-Gloss Epoxy		SHW-85-NA-GHS-US	

Section 8. Exposure controls/personal protection

Ingredient name		Exposure limits		
None.				
Occupational exposure lin	nits (Mexico)			
Ingredient name		Exposure limits		
None.				
Appropriate engineering controls	local exhaust ventilation or	dust, fumes, gas, vapor or mist, use process enclosures, other engineering controls to keep worker exposure to w any recommended or statutory limits.		
Environmental exposure controls	they comply with the requir cases, fume scrubbers, filte	or work process equipment should be checked to ensure ements of environmental protection legislation. In some ers or engineering modifications to the process equipment emissions to acceptable levels.		
Individual protection meas	<u>ures</u>			
Hygiene measures				
Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.				
Skin protection				
Hand protection	worn at all times when han necessary. Considering th during use that the gloves a noted that the time to breal glove manufacturers. In th	ious gloves complying with an approved standard should be dling chemical products if a risk assessment indicates this is e parameters specified by the glove manufacturer, check are still retaining their protective properties. It should be kthrough for any glove material may be different for different e case of mixtures, consisting of several substances, the s cannot be accurately estimated.		
Body protection		ent for the body should be selected based on the task being volved and should be approved by a specialist before		
Other skin protection		iny additional skin protection measures should be selected informed and the risks involved and should be approved by a his product.		
Respiratory protection	appropriate standard or ce	otential for exposure, select a respirator that meets the tification. Respirators must be used according to a am to ensure proper fitting, training, and other important		

Section 9. Physical and chemical properties

Appearance			
Physical state	: Liquid.		
Color	: Not available.		
Odor	: Not available.		
Odor threshold	: Not available.		
рН	: 9.5		
Melting point/freezing point	: Not available.		
Boiling point/boiling range	: 100°C (212°F)		
Flash point	: Closed cup: >93.3°C (>199.9°F)		
Date of issue/Date of revision	: 9/10/2018 Date of previous issue : 7/4/2018	Version : 10.03 5/	/11
K46W151 PRO INDUSTRIAL Extra White	™ Pre-Catalyzed Waterbased Semi-Gloss Epoxy	SHW-85-NA-GHS-US	

Section 9. Physical and chemical properties

,	
Evaporation rate	: 0.09 (butyl acetate = 1)
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: 0.6% Upper: 20.4%
Vapor pressure	: 2.3 kPa (17.5 mm Hg) [at 20°C]
Vapor density	: 1 [Air = 1]
Relative density	: 1.24
Solubility	: Not available.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Kinematic (40°C (104°F)): >0.205 cm ² /s (>20.5 cSt)
Molecular weight	: Not applicable.
Aerosol product	
Heat of combustion	: 2.193 kJ/g

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 Micrograms Intermittent	-
2-(2-Methoxyethoxy)-ethanol	Eyes - Mild irritant	Rabbit	-	24 hours 500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	500 milligrams	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Date of issue/Date	of revision	: 9/10/2018	Date of previous issue	: 7/4/2018	Version : 10.03	6/11
K46W151	PRO INDUSTRIAL™ Pro Extra White	e-Catalyzed Wat	erbased Semi-Gloss Epoxy		SHW-85-NA-GHS-US	

Section 11. Toxicological information

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide	-	2B	-

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
2-(2-Methoxyethoxy)-ethanol	Category 3		Respiratory tract irritation and Narcotic effects

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
2-(2-Methoxyethoxy)-ethanol	Category 2	Not determined	Not determined

Aspiration hazard

Extra White

Not available.

Information on the likely routes of exposure	: Not available.	
Potential acute health effe	<u>cts</u>	
Eye contact	: No known significant effects or critical hazards.	
Inhalation	: No known significant effects or critical hazards.	
Skin contact	: No known significant effects or critical hazards.	
Ingestion	: No known significant effects or critical hazards.	
Symptoms related to the p	physical, chemical and toxicological characteristics	
Eye contact	: No specific data.	
Inhalation	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Skin contact	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Ingestion	: Adverse symptoms may include the following: reduced fetal weight increase in fetal deaths skeletal malformations	
Delayed and immediate ef	fects and also chronic effects from short and long term exposure	<u>}</u>
<u>Short term exposure</u>		
Potential immediate effects	: Not available.	
Potential delayed effects	: Not available.	
Date of issue/Date of revision	: 9/10/2018 Date of previous issue : 7/4/2018	Version : 10.03
K46W151 PRO INDUSTR	IAL™ Pre-Catalyzed Waterbased Semi-Gloss Epoxy	SHW-85-NA-GHS-US

7/11

<u>Long term exposure</u>	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health ef	<u>fects</u>
Not available.	
General	: May cause damage to organs through prolonged or repeated exposure.
Carcinogenicity	: Suspected of causing cancer. Risk of cancer depends on duration and level of exposure.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: Suspected of damaging the unborn child.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity			
Product/ingredient name	Result	Species	Exposure
Titanium Dioxide 2-(2-Methoxyethoxy)-ethanol	Acute LC50 >1000000 μg/l Marine water Acute EC50 >930 ppm Fresh water Acute LC50 7500000 μg/l Fresh water	Fish - Fundulus heteroclitus Daphnia - Daphnia magna Fish - Lepomis macrochirus	96 hours 48 hours 96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition : Not available. coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains
	and sewers.

Date of issue/Date	of revision	: 9/10/2018	Date of previous issue	: 7/4/2018	Version	: 10.03	8/11
K46W151	PRO INDUSTRIAL™ Pre Extra White	e-Catalyzed Wate	rbased Semi-Gloss Epoxy		SHW-85-	NA-GHS-US	

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	IATA	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user :

: Multi-modal shipping descriptions are provided for informational purposes and do not consider container sizes. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

Transport in bulk according : Not available. to Annex II of MARPOL and the IBC Code

Proper shipping name	: Not available.
Ship type	: Not available.
Pollution category	: Not available.

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 5-Chloro-2-methylisothiazolinone

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65


WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations

International lists		: Australia inventory (AICS): Not determined. China inventory (IECSC): Not determined.
		Japan inventory (ENCS): Not determined.
		Japan inventory (ISHL): Not determined.
		Korea inventory (KECI): Not determined.
		Malaysia Inventory (EHS Register): Not determined.
		New Zealand Inventory of Chemicals (NZIoC): Not determined.
		Philippines inventory (PICCS): Not determined.
		Taiwan Chemical Substances Inventory (TCSI): Not determined.
		Thailand inventory: Not determined.
		Turkey inventory: Not determined.
		Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

	Classification Justification		
	gory 2Calculation methodN (Unborn child) - Category 2Calculation methodN TOXICITY (REPEATED EXPOSURE) - Category 2Calculation method		
<u>History</u>			
Date of printing	: 9/10/2018		
Date of issue/Date of revision	: 9/10/2018		
Date of previous issue	: 7/4/2018		
Version	: 10.03		
Key to abbreviations	 ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations 		

Notice to reader

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.

Date of issue/Date	of revision	:9/10/2018	Date of previous issue
K46W151	PRO INDUSTRIAL™ Pre Extra White	-Catalyzed Water	based Semi-Gloss Epoxy

: 7/4/2018