



Professional Quality Art Supplies Since 1949

## Material Safety Data Sheet

For Health Emergencies: CALL A POISON CONTROL CENTER

Date Prepared  
Rev: 15 October 2009  
Replaces: 24 August 2009

---

## Material Safety Data Sheet

### Section 1 - PRODUCT AND COMPANY IDENTIFICATION

- 1.1 PRODUCT NAME: Utrecht Damar Varnish
- 1.2 ITEM NUMBER AND SIZES: 11400 – 118ml, 11399 – 236ml, 11401 – 473ml
- 1.3 MANUFACTURER IDENTIFICATION:  
Utrecht Manufacturing Corp.  
6 Corporate Drive • Cranbury, New Jersey 08512 USA  
Phone: 877-887-7328 • Web: <http://www.utrecht.com>

---

### SECTION 2 – COMPOSTION INFORMATION

COMPONENT	CAS #	MAX. AMOUNT (% Weight)
Pure Gum Spirits of Turpentine (Contains Delta 3-Carene)	9005-90-7	50

---

### SECTION 3 – HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Appearance:** Clear light yellow colored liquid

**Physical State:** Liquid

**Odor:** Typical pine derivative or turpentine odor

**Hazards of Product:** Flammable, Harmful or Fatal if Swallowed. May be Harmful by breathing vapors.

#### 3.2 POTENTIAL HEALTH EFFECTS

##### EFFECTS OF SINGLE ACUTE OVEREXPOSURE:

May be harmful or fatal if swallowed. May be harmful by breathing vapors. Eye irritant. Overexposure may result in nausea headache confusion or instability. May cause allergic reactions.

##### CHRONIC, PROLONGED OR REPEATED OVEREXPOSURE:

May be harmful by breathing vapors. Eye irritant. Overexposure may result in nausea headache confusion or instability. May cause allergic reactions.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: n/a

3. 3 POTENTIAL ENVIRONMENTAL EFFECTS: n/a

---

#### SECTION 4 – FIRST AID PROCEDURES

4.1 INHALATION: Move to fresh air. Get prompt medical attention.

4.2 EYE CONTACT: Wash eyes with tap water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.

4.3 SKIN CONTACT: Wash affected area with soap and water for five to ten (5 – 10) minutes. If irritation persists, seek prompt medical attention.

4.4 SWALLOWING: If swallowed, do not induce vomiting. Get prompt medical attention.

4.2 NOTES TO PHYSICIAN: n/a

---

#### SECTION 5 - FIRE FIGHTING MEASURES

##### 5.1 FLAMMABLE PROPERTIES

<b>Identification Number:</b>	UN 1263
<b>Flash Point – Closed Cup:</b>	91°F (33°C)
<b>Flash Point – Open Cup:</b>	n/a
<b>Auto-Ignition Temperature:</b>	n/a
<b>Flammable Limits in Air:</b>	LEL 0.8% - UEL 6%

5.2 EXTINGUISHING MEDIA Foam, CO<sub>2</sub>, Dry Chemical (Class B) or Halon®, Water Fog

5.3 EXTINGUISHING MEDIA TO AVOID n/a

5.4 SPECIAL FIRE FIGHTING PROCEDURES n/a

5.5 SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS As with any fire situation, full face, self contained breathing apparatus and appropriate protective clothing should be worn.

5.6 UNUSUAL FIRE AND EXPLOSION HAZARDS n/a

5.7 HAZARDOUS COMBUSTION PRODUCTS Under fire conditions, this product may release CO, CO<sub>2</sub>, and other decomposition products of undetermined hazard.

---

#### SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Keep sources of ignition away. Small quantities may be cleaned up with rags or paper towels and transferred to airtight containers for disposal. Rags or paper towels soaked with this material should be placed in approved waste cans and / or soaked with water, for disposal in accordance with local state and federal regulations.

---

## SECTION 7 – HANDLING AND STORAGE

7.1 GENERAL HANDLING: Avoid ingestion. Avoid breathing vapors. Use exhaust fan to remove vapors and assure adequate ventilation. Do not transfer contents to unlabeled containers. KEEP OUT OF THE REACH OF CHILDREN. Keep from sources of ignition, oxidizing materials, heat and flame. KEEP AWAY FROM OPEN FLAMES. NO SMOKING in areas of use or storage.

7.2 STORAGE: Keep from sources of ignition, oxidizing materials, heat and flame. Keep containers closed when not in use.

---

## SECTION 8 – EXPOSURE CONTROLS AND PERSONAL PROTECTION

8.1 EXPOSURE LIMITS: 100 PPM ACGIH TLV

8.2 PERSONAL PROTECTION:

**Respiratory Protection:** If TLV is exceeded, MSHA / NIOSH approved organic vapor respiratory protection should be worn.  
**Ventilation:** Use exhaust fan to remove vapors and assure adequate ventilation.  
**Eye Protection:** Use OSHA approved chemical splash goggles with side shields  
**Protective Gloves:** Neoprene or rubber – impervious gloves  
**Other Protective Equipment:** Body protection suitable for the work environment

8.3 ENGINEERING CONTROLS: n/a

---

## SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Physical State:** Liquid  
**Appearance:** Clear light yellow liquid  
**pH:** n/a  
**Solubility in Water (by weight):** Negligible  
**Odor:** Typical pine derivative or turpentine odor  
**Flash Point – Closed Cup:** 91°F (33°C)  
**Flash Point – Open Cup:** n/a  
**Percent Volatiles:** 50%  
**Boiling Point (760mm Hg):** 311° - 338°F (155° - 170°C)  
**Freezing Point:** n/a  
**Specific Gravity (H<sub>2</sub>O = 1):** 0.93  
**Vapor Pressure at 20°C:** 4mg Hg  
**Vapor Density (air = 1):** 4.7  
**Evaporation Rate (Butyl Acetate = 1):** <1  
**Melting Point:** n/a

---

## Section 10 – STABILITY AND REACTIVITY

10.1 STABILITY / INSTABILITY: Stable under ordinary conditions of use and storage  
**Conditions to Avoid:** Keep from heat, open flame and sources of ignition  
**Incompatible Materials:** Strong oxidizing agents, acids or acidic materials

10.2 HAZARDOUS POLYMERIZATION: Will not occur

10.3 INHIBITORS / STABILIZERS: n/a

---

## SECTION 11 – TOXICOLOGICAL INFORMATION

ACUTE TOXICITY: **FLAMMABLE**. Harmful or fatal if swallowed. May be harmful by breathing vapors. Eye and skin irritant. May cause allergic reactions. Overexposure may result in nausea, headache, confusion or instability.

CHRONIC TOXICITY: May cause allergic reactions. Overexposure may result in nausea, headache, confusion or instability.

---

## SECTION 12 – ECOLOGICAL INFORMATION

12.1 ENVIRONMENTAL FATE	n/a
12.2 ECOTOXICITY	n/a
12.3 FURTHER INFORMATION	n/a

---

## SECTION 13 – DISPOSAL CONSIDERATIONS

13.1 WASTE DISPOSAL METHOD	Dispose of in accordance with local, state and federal regulations
13.2 DISPOSAL CONSIDERATIONS	Keep from heat, open flame, sparks and sources of ignition

---

## SECTION 14 – TRANSPORTATION INFORMATION

U.S. D.O.T	Domestic Ground: ORM-D Consumer Commodity Ocean Freight: UN 1263 Paint Related Material, Class 3, PG III, Limited Quantity DO NOT SHIP via air freight without special packaging and labeling. Contact your air carrier for detailed instructions.
------------	--

---

## SECTION 15 – REGULATORY INFORMATION

15.1 FEDERAL / NATIONAL	n/a
15.2 STATE / LOCAL	n/a

---

## SECTION 16 – OTHER INFORMATION

The information presented here is current as of the date of this Material Safety Data Sheet and is believed to be accurate but is not warranted to be, whether originating with the company or not. Since use of this information and the product are not under the control of Utrecht Manufacturing Corp., it is the user's obligation to determine conditions of safe use, in advance of use, and to carefully read the product label and follow all instructions for safe use of the product.