Section 1. Identification

Product identifier

Product Identity 248 Moly Syngard 2000 NLGI Grades 1,2 and 3

Other means of identification Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Extreme pressure lubricating grease.

Details of the supplier of the safety data sheet

Company Name

Schaeffer Mfg. Company
2600 S. Broadway
Saint Louis, MO 63118

Emergency

24 hour Emergency Telephone No. 314-865-4105

Customer Service:

Tel: 314-865-4100
Toll Free: 1-800-325-9962
Fax: 314-865-4107
E-Mail:safety@schaefferoil.com
Web: http://www.schaefferoil.com

Section 2. Hazard(s) identification

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

The substance is not classified according to the OSHA Hazcom or WHMIS regulations.
**Due to the physical state of the product, Silica Quartz in this material cannot cause cancer.*

Label elements

The substance is not classified according to the OSHA Hazcom or WHMIS regulations.

[Prevention]

No GHS prevention statements

[Response]

No GHS response statements

[Storage]

No GHS storage statements

[Disposal]

No GHS disposal statements

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.

Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7).

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Residual oils (petroleum), solvent dewaxed **CAS Number: 64742-62-7** **Synonyms: Residual oils (petroleum), solvent-dewaxed**	**45 - 70**	**Not Classified**	**No data available**
Distillates (petroleum), solvent-dewaxed heavy paraffinic **CAS Number: 64742-65-0** **Synonyms: No available information**	**30 - 60**	**Not Classified**	**No data available**
Distillates (petroleum), hydrotreated heavy paraffinic **CAS Number: 64742-54-7** **Synonyms: No available information**	**3 - 7**	**Not classified**	**No data available**
Acetone **CAS Number: 67-64-1** **Synonyms: 2-Propanone, Dimethyl ketone, Dimethylformaldehyde, Propanone**	**0.5 - 1.5**	**Flammable Liquid, category 2;H225** **Specific target organ toxicity, Single exposure category 3;H336** **Serious eye damage / eye irritation, category 2;H319**	**No data available**
Crystalline Silica **CAS Number: 14808-60-7** **Synonyms: Quartz, Silicondioxide**	**0.1 - 1**	**Not Classified**	**No data available**

The actual concentration or concentration range is withheld as a trade secret.
*PBT/vPvB - PBT, vPvM or vPvB-substance.
The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

Inhalation Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview No specific symptom data available.
No chronic toxicity or long term toxicity information available. Treat symptomatically. See section 2 for further details.

Section 5. Fire-fighting measures

Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO_2, powder, water spray.
Unsuitable extinguishing media: Do not use; water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

ERG Guide No. ----

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8. Contain and absorb spillage with non-combustible materials e.g. sand, earth, and vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Incompatible materials: No available information

See section 2 for further details. - [Storage]

Specific end use(s)

No available information

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	OSHA	1000 ppm, 2400 mg/m^3
		ACGIH	TWA: 250 ppm STEL: 500 ppm
		NIOSH	250 ppm (590 mg/m^3) TWA
14808-60-7	Crystalline Silica	OSHA	250/(%SiO2+5) mppcf, 10 (%SiO2+2) mg/m^3
		ACGIH	TWA:0.025 mg/m^3 (R) Respirable fraction
		NIOSH	0.05 mg/m^3 TWA (respirable)
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
64742-62-7	Residual oils (petroleum), solvent dewaxed	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m^3 OSHA PEL and 5 mg/m^3 ACGIH.

Exposure controls

Respiratory If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes Protective safety glasses recommended

Skin Avoid skin contact. Protective gloves recommended.

Engineering Controls Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Amber
Odor	Mild Petroleum
Odor threshold	No available information
Melting point / freezing point	No available information
Initial boiling point and boiling range	Base Oils 315°C (599°F)
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: No available information

Flash Point	Upper Explosive Limit: No available information Open cup: 265 to 277°C (509 to 530.6°F) [Cleveland.]
Auto-ignition temperature	No available information
Decomposition temperature	No available information
pH	No available information
Kinematic viscosity	No available information
Solubility in Water	Negligible in water.
Partition coefficient n-octanol/water (Log Kow)	No available information
Vapor pressure (Pa)	No available information
Relative Density	0.9 to 1.02
Vapor Density	>1 [Air = 1]
Evaporation rate (Ether = 1)	No available information
Oxidising properties	No available information
Explosive properties	No available information

Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No available information

Conditions to avoid

No data available.

Incompatible materials

No available information

Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Residual oils (petroleum), solvent dewaxed - (64742-62-7)	No data available.	No data available.	No data available.	No data available.	No data available.
Distillates (petroleum), solvent-dewaxed heavy paraffinic - (64742-65-0)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.
Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7)	> 5,000.00, Rat - Category: NA	> 5,000.00, Rabbit - Category: NA	No data available.	No data available.	No data available.
Acetone - (67-64-1)	5,800.00, Rat - Category: NA	7,426.00, Rabbit - Category: NA	76.00, Rat - Category: NA	50.10, Rat - Category: NA	No data available.
Crystalline Silica - (14808-60-7)	No data available.	100,000.00 - Category: NA	No data available.	No data available.	No data available.

Carcinogen Data

CAS No.	Ingredient	Source	Value
67-64-1	Acetone	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	A4
14808-60-7	Crystalline Silica	OSHA	Regulated Carcinogen: No;
		NTP	Known: Yes; Suspected: No;
		IARC	No
		ACGIH	A2
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
64742-62-7	Residual oils (petroleum), solvent dewaxed	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit
64742-65-0	Distillates (petroleum), solvent-dewaxed heavy paraffinic	OSHA	Regulated Carcinogen: No;
		NTP	Known: No; Suspected: No;
		IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry:
Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:
No specific symptom data available.
No chronic toxicity or long term toxicity information available. Treat symptomatically.

Section 12. Ecological information

Toxicity
No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Residual oils (petroleum), solvent dewaxed - (64742-62-7)	No data available.	No data available.	No data available.
Distillates (petroleum), solvent-dewaxed heavy paraffinic - (64742-65-0)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00, Scenedesmus subspicatus
Distillates (petroleum), hydrotreated heavy paraffinic - (64742-54-7)	101.00, Pimephales promelas	> 10,000, Daphnia magna	100.00, Pseudokirchneriella subcapitata
Acetone - (67-64-1)	8,120.00, Pimephales promelas	8,800.00, Daphnia pulex	7,000.00, Pseudokirchneriella subcapitata
Crystalline Silica - (14808-60-7)	No data available.	No data available.	No data available.

Persistence and degradability
There is no data available on the preparation itself.

Bioaccumulative potential
No available information

Mobility in soil
No available information

Results of PBT and vPvB assessment
This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects
No available information

Section 13. Disposal considerations

Waste treatment methods
The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable product via a licensed waste disposal contractor. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	US DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
Transport hazard class(es)	Class: Not Applicable Sub Class: Not Applicable	Class: Not Applicable Sub Class: Not Applicable	Class: Not Applicable Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable

Environmental hazards

IMDG Marine Pollutant: No;

Special precautions for user

No available information

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

Classification of the substance or mixture under OSHA's Hazard Communication Standard (1910.1200) revised 2024 (GHS revision 7)

All components of this material are either listed or exempt from listing on the TSCA Inventory.

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Antimony, tris(dipentylcarbamodithioato-s,s')-, (o

Proposition 65 Label Warning:



WARNING: This product can expose you to chemicals including [Crystalline Silica], which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Mass RTK Substances (>1%) :

Acetone

New Jersey RTK Substances (>1%):

Acetone

Pennsylvania RTK Substances (>1%):

Acetone

Section 16. Other information

Issue Date	25 August, 2026 30
Revision Date	September, 2026
SDS Version:	3

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H336 May cause drowsiness and dizziness.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document