

## SAFETY DATA SHEET

Version 6.10  
Revision Date 03/02/2024  
Print Date 07/13/2024

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Glacial Acetic Acid

Product Number : PHR1748  
Brand : Sigma-Aldrich  
Index-No. : 607-002-00-6  
CAS-No. : 64-19-7

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Identified uses : Laboratory chemicals, Synthesis of substances

Uses advised against : The product is being supplied under the TSCA R&D Exemption (40 CFR Section 720.36). It is the recipient's responsibility to comply with the requirements of the R&D exemption. The product may not be used for a non-exempt commercial purpose under TSCA unless appropriate consent is granted in writing by MilliporeSigma.

**1.3 Details of the supplier of the safety data sheet**

Company : Sigma-Aldrich Inc.  
3050 SPRUCE ST  
ST. LOUIS MO 63103  
UNITED STATES

Telephone : +1 314 771-5765  
Fax : +1 800 325-5052

**1.4 Emergency telephone**

Emergency Phone # : 800-424-9300 CHEMTREC (USA) +1-703-  
527-3887 CHEMTREC (International) 24  
Hours/day; 7 Days/week

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)**

Flammable liquids (Category 3), H226  
Skin corrosion (Category 1A), H314  
Serious eye damage (Category 1), H318

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H226

Flammable liquid and vapor.

H314

Causes severe skin burns and eye damage.

Precautionary Statements

P210

Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233

Keep container tightly closed.

P240

Ground/bond container and receiving equipment.

P241

Use explosion-proof electrical/ ventilating/ lighting/ equipment.

P242

Use only non-sparking tools.

P243

Take precautionary measures against static discharge.

P264

Wash skin thoroughly after handling.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

P301 + P330 + P331

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 +

P310

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P363

Wash contaminated clothing before reuse.

P370 + P378

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

P403 + P235

Store in a well-ventilated place. Keep cool.

P405

Store locked up.

P501

Dispose of contents/ container to an approved waste disposal plant.

## 2.3 Hazards not otherwise classified (HNOC) or not covered by GHS - none

### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Formula	: C <sub>2</sub> H <sub>4</sub> O <sub>2</sub>
Molecular weight	: 60.05 g/mol
CAS-No.	: 64-19-7
EC-No.	: 200-580-7
Index-No.	: 607-002-00-6

Component	Classification	Concentration
-----------	----------------	---------------

acetic acid		
	Flam. Liq. 3; Skin Corr. 1A; Eye Dam. 1; H226, H314, H318 Concentration limits: >= 90 %: Skin Corr. 1A, H314; 25 - < 90 %: Skin Corr. 1B, H314; 10 - < 25 %: Skin Irrit. 2, H315; 10 - < 25 %: Eye Irrit. 2, H319;	<= 100 %

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

First aiders need to protect themselves. Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Call a physician immediately.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Immediately call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: make victim drink water (two glasses at most), avoid vomiting (risk of perforation). Call a physician immediately. Do not attempt to neutralise.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Water Foam Carbon dioxide (CO2) Dry powder

**Unsuitable extinguishing media**

For this substance/mixture no limitations of extinguishing agents are given.

**5.2 Special hazards arising from the substance or mixture**

Carbon oxides

Combustible.

Vapors are heavier than air and may spread along floors.

Forms explosive mixtures with air at elevated temperatures.

Development of hazardous combustion gases or vapours possible in the event of fire.

**5.3 Advice for firefighters**

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

**5.4 Further information**

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition.

Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

**6.2 Environmental precautions**

Do not let product enter drains. Risk of explosion.

**6.3 Methods and materials for containment and cleaning up**

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent and neutralising material (e.g. Chemizorb® H<sup>+</sup>, Merck Art. No. 101595). Dispose of properly. Clean up affected area.

**6.4 Reference to other sections**

For disposal see section 13.

---

**SECTION 7: Handling and storage****7.1 Precautions for safe handling****Advice on protection against fire and explosion**

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

**Hygiene measures**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

**7.2 Conditions for safe storage, including any incompatibilities****Storage conditions**

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Store at Room Temperature.

### Storage class

Storage class (TRGS 510): 3: Flammable liquids

## 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
acetic acid	64-19-7	TWA	10 ppm	USA. ACGIH Threshold Limit Values (TLV)
		STEL	15 ppm	USA. ACGIH Threshold Limit Values (TLV)
		TWA	10 ppm 25 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		ST	15 ppm 37 mg/m <sup>3</sup>	USA. NIOSH Recommended Exposure Limits
		TWA	10 ppm 25 mg/m <sup>3</sup>	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		PEL	10 ppm 25 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		C	40 ppm	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	15 ppm 37 mg/m <sup>3</sup>	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

#### Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute local effects	25 mg/m <sup>3</sup>
Workers	Inhalation	Long-term local effects	25 mg/m <sup>3</sup>
Workers	Skin contact	Long-term local effects	10mg/kg BW/d
Consumers	Inhalation	Acute local effects	25 mg/m <sup>3</sup>
Consumers	Inhalation	Long-term local effects	25 mg/m <sup>3</sup>

**Predicted No Effect Concentration (PNEC)**

Compartment	Value
Soil	0.478 mg/kg
Sea water	0.3058 mg/l
Fresh water	3.058 mg/l
Sea sediment	1.136 mg/kg
Fresh water sediment	11.36 mg/kg
Sewage treatment plant	85 mg/l
Aquatic intermittent release	30.58 mg/l

**8.2 Exposure controls****Appropriate engineering controls**

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

**Personal protective equipment****Eye/face protection**

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Tightly fitting safety goggles

**Skin protection**

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Butoject® (KCL 898)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Latex gloves

Minimum layer thickness: 0.6 mm

Break through time: 30 min

Material tested: Lapren® (KCL 706 / Aldrich Z677558, Size M)

**Body Protection**

Flame retardant antistatic protective clothing.

**Respiratory protection**

Recommended Filter type: filter E-(P2)

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer.

These measures have to be properly documented.

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

#### **Control of environmental exposure**

Do not let product enter drains. Risk of explosion.

---

## **SECTION 9: Physical and chemical properties**

### **9.1 Information on basic physical and chemical properties**

a) Appearance	Form: liquid Color: colorless
b) Odor	stinging
c) Odor Threshold	0.2 ppm
d) pH	2.5 at 50 g/l at 20 °C (68 °F)
e) Melting point/freezing point	Melting point: 16.64 °C (61.95 °F)
f) Initial boiling point and boiling range	117.9 °C 244.2 °F at 1,013.25 hPa
g) Flash point	39 °C (102 °F) - closed cup
h) Evaporation rate	No data available
i) Flammability (solid, gas)	Not applicable
j) Upper/lower flammability or explosive limits	Upper explosion limit: 19.9 %(V) Lower explosion limit: 4 %(V)
k) Vapor pressure	20.79 hPa at 25 °C (77 °F)
l) Vapor density	2.07
m) Density	1.04 g/cm <sup>3</sup> at 25 °C (77 °F)
Relative density	No data available
n) Water solubility	602.9 g/l at 25 °C (77 °F) at 1,013 hPa - completely soluble
o) Partition coefficient: n-octanol/water	log Pow: -0.17 at 25 °C (77 °F) - Bioaccumulation is not expected., (ECHA)
p) Autoignition temperature	463 °C (865 °F)
q) Decomposition temperature	Distillable in an undecomposed state at normal pressure.
r) Viscosity	1.17 mm <sup>2</sup> /s at 20 °C (68 °F) -
s) Explosive properties	No data available
t) Oxidizing properties	none

## 9.2 Other safety information

Surface tension	28.8 mN/m at 10.0 °C (50.0 °F)
Relative vapor density	2.07

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapor/air-mixtures are explosive at intense warming.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

### 10.3 Possibility of hazardous reactions

Risk of explosion with:

peroxi compounds  
perchloric acid  
fuming sulfuric acid  
phosphorus halides  
hydrogen peroxide  
chromium(VI) oxide  
potassium permanganate  
Peroxides

Strong oxidizing agents

Risk of ignition or formation of inflammable gases or vapours with:

Iron  
Zinc  
magnesium

Mild steel

Possible formation of:

Hydrogen

Violent reactions possible with:

strong alkalis  
Aldehydes  
alkali hydroxides  
nonmetallic halides  
ethanolamine  
Acetaldehyde  
Alcohols  
halogen-halogen compounds  
chlorosulfonic acid  
chromosulfuric acid  
Potassium hydroxide  
Nitric acid

### 10.4 Conditions to avoid

Heating.



## 10.5 Incompatible materials

various metals

## 10.6 Hazardous decomposition products

In the event of fire: see section 5

---

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

LD50 Oral - Rat - 3,310 mg/kg

Remarks: (RTECS)

LC50 Inhalation - Mouse - 4 h - 2,819 mg/l - vapor

Remarks: (RTECS)

Dermal: No data available

#### Skin corrosion/irritation

Skin - Rabbit

Result: Causes burns. - 4 h

(OECD Test Guideline 404)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

#### Serious eye damage/eye irritation

Eyes - Rabbit

Result: Causes burns. - 4 h

(OECD Test Guideline 405)

Remarks: (IUCLID)

Remarks: Causes serious eye damage.

#### Respiratory or skin sensitization

No data available

#### Germ cell mutagenicity

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Test Type: Micronucleus test

Species: Rat

Cell type: Bone marrow

Application Route: inhalation (vapor)

Method: Mutagenicity (micronucleus test)

Result: negative

#### Carcinogenicity

Sigma-Aldrich - PHR1748

Page 9 of 13

- IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
- NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
- OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### **Reproductive toxicity**

No data available

#### **Specific target organ toxicity - single exposure**

No data available

#### **Specific target organ toxicity - repeated exposure**

No data available

#### **Aspiration hazard**

No data available

### **11.2 Additional Information**

Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., spasm, inflammation and edema of the larynx, spasm, inflammation and edema of the bronchi, pneumonitis, pulmonary edema, burning sensation, Cough, wheezing, laryngitis, Shortness of breath, Headache, Nausea, Vomiting, Ingestion or inhalation of concentrated acetic acid causes damage to tissues of the respiratory and digestive tracts. Symptoms include: hematemesis, bloody diarrhea, edema and/or perforation of the esophagus and pylorus, pancreatitis, hematuria, anuria, uremia, albuminuria, hemolysis, convulsions, bronchitis, pulmonary edema, pneumonia, cardiovascular collapse, shock, and death. Direct contact or exposure to high concentrations of vapor with skin or eyes can cause: erythema, blisters, tissue destruction with slow healing, skin blackening, hyperkeratosis, fissures, corneal erosion, opacification, iritis, conjunctivitis, and possible blindness.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

---

## **SECTION 12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish	semi-static test LC50 - Oncorhynchus mykiss (rainbow trout) - > 1,000 mg/l - 96 h (OECD Test Guideline 203)
Toxicity to daphnia and other aquatic invertebrates	static test EC50 - Daphnia magna (Water flea) - > 1,000 mg/l - 48 h (OECD Test Guideline 202)
Toxicity to algae	static test EC50 - Skeletonema costatum - > 1,000 mg/l - 72 h

Sigma-Aldrich - PHR1748

Page 10 of 13

	(ISO 10253)
Toxicity to bacteria	EC5 - Pseudomonas putida - 2,850 mg/l - 16 h Remarks: neutral (maximum permissible toxic concentration) (Lit.)
	microtox test EC50 - Photobacterium phosphoreum - 11 mg/l - 15 min Remarks: (IUCLID)

## 12.2 Persistence and degradability

Biodegradability	Result: 99 % - Readily biodegradable. (OECD Test Guideline 301D) Remarks: (HSDB)
	Result: 95 % - Readily eliminated from water (OECD Test Guideline 302B)
Biochemical Oxygen Demand (BOD)	880 mg/g Remarks: (Lit.)
Ratio BOD/ThBOD	76 % Remarks: (IUCLID)

## 12.3 Bioaccumulative potential

No data available

## 12.4 Mobility in soil

No data available

## 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

## 12.6 Endocrine disrupting properties

No data available

## 12.7 Other adverse effects

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

#### Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

---

**SECTION 14: Transport information****DOT (US)**

UN number: 2789    Class: 8 (3)    Packing group: II  
Proper shipping name: Acetic acid, glacial  
Reportable Quantity (RQ): 5000 lbs  
Poison Inhalation Hazard: No

**IMDG**

UN number: 2789    Class: 8 (3)    Packing group: II EMS-No: F-  
E, S-C  
Proper shipping name: ACETIC ACID, GLACIAL

**IATA**

UN number: 2789    Class: 8 (3)    Packing group: II  
Proper shipping name: Acetic acid, glacial

---

**SECTION 15: Regulatory information****SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

**SARA 313 Components**

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**SARA 311/312 Hazards**

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

**Massachusetts Right To Know Components**

acetic acid	CAS-No. 64-19-7	Revision Date 1993-04-24
-------------	--------------------	-----------------------------

**Pennsylvania Right To Know Components**

acetic acid	CAS-No. 64-19-7	Revision Date 1993-04-24
-------------	--------------------	-----------------------------

---

## SECTION 16: Other information

### Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).

Version: 6.10

Revision Date: 03/02/2024

Print Date: 07/13/2024