

Safety Data Sheet

22148-XXXX

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 1 of 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Blick Studio Art Marker Ink (all colors)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Art Marker Ink

1.3. Details of the supplier of the safety data sheet

Company name:	A.W. Faber-Castell Peruana S.A.	
	Peruana	
Street:	Av. La Molina 161	
Place:	PE Lima 3	
Telephone:	0051-1-612-1900	Telephone: 0051-1-6121900-2213
Contact person:	Pamela Araujo	
e-mail:	Pamela.Araujo@Faber-Castell.com.pe; marketing@faber-castell.com.pe	
Internet:	www.faber-castell.com.pe	
1.4. Emergency telephone number:	0051-1-6121900-2213	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture**

Regulation (EC) No. 1272/2008

Hazard categories:

Flammable liquid: Flam. Liq. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements


Regulation (EC) No. 1272/2008

Hazard components for labelling

1-methoxy-2-propanol; monopropylene glycol methyl ether
propan-2-ol; isopropyl alcohol; isopropanol

Signal word: Danger

Pictograms:



Hazard statements

Highly flammable liquid and vapour.

Causes serious eye irritation.

May cause drowsiness or dizziness.

Precautionary statements

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Revision No. 1.00

Print date: 12.04.2018

Item Numbers: 22148-0000, 22148-1006, 22148-1012, 22148-1024, 22148-1048, 22148-1096, 22148-1120, 22148-1130, 22148-1200, 22148-1620, 22148-2020, 22148-2110, 22148-2120, 22148-2130, 22148-2140, 22148-2150, 22148-2160, 22148-2280, 22148-2329, 22148-2410, 22148-2420, 22148-2430, 22148-2440, 22148-2450, 22148-2460, 22148-2470, 22148-2480, 22148-2490, 22148-2590, 22148-2710, 22148-2720, 22148-2730, 22148-2740, 22148-2750, 22148-2760, 22148-2770, 22148-2780, 22148-2790, 22148-2809, 22148-3010, 22148-3040, 22148-3060, 22148-3170, 22148-3240, 22148-3350, 22148-3510, 22148-3610, 22148-3680, 22148-3700, 22148-3710, 22148-3720, 22148-3730, 22148-3760, 22148-3780, 22148-3790, 22148-4040, 22148-4070, 22148-4110, 22148-4120, 22148-4260, 22148-4510, 22148-4700, 22148-4960, 22148-5040, 22148-5080, 22148-5110, 22148-5160, 22148-5230, 22148-5380, 22148-5450, 22148-5480, 22148-5760, 22148-5770, 22148-5820, 22148-6000, 22148-6030, 22148-6510, 22148-7030, 22148-7040, 22148-7070, 22148-7080, 22148-7150, 22148-7170, 22148-7230, 22148-7250, 22148-7330, 22148-7400, 22148-7480, 22148-7630, 22148-7910, 22148-8030, 22148-8080, 22148-8090, 22148-8110, 22148-8120, 22148-8230, 22148-8300, 22148-8340, 22148-8380, 22148-8430, 22148-8540, 22148-8710, 22148-8910

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 2 of 9

Wear protective gloves/protective clothing/eye protection/face protection.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place. Keep cool.
 Store locked up.

2.3. Other hazards

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization
Preparation.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether			70 - < 75 %
	203-539-1	603-064-00-3		
	Flam. Liq. 3, STOT SE 3; H226 H336			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			20 - < 25 %
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
1589-47-5	2-methoxypropanol			< 1 %
	216-455-5	603-106-00-0		
	Flam. Liq. 3, Repr. 1B, STOT SE 3, Skin Irrit. 2, Eye Dam. 1; H226 H360D *** H335 H315 H318			

Full text of H and EUH statements: see section 16.

Further information

Depending on the color, the following hazardous coloring agents can be included:

Basic Blue 7	<2%	CAS2390-60-5	H302, H315, H319
Basic Yellow 37	<2%	CAS6358-36-7	H318, H411
Solvent Red 218	<3%	CAS73049-38-4	H312, H332

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

Rinse mouth immediately and drink plenty of water.

Revision No. 1,00

Print date: 12.04.2018

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 3 of 9

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Danger of explosion

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7
Personal protection equipment: see section 8
Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Advice on storage compatibility

Do not store together with: @O102.B010927. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Art Marker Ink

Revision No 1.00

Print date: 12.04.2018

Item Numbers: 22148-0000, 22148-1006, 22148-1012, 22148-1024, 22148-1048, 22148-1096, 22148-1120, 22148-1130, 22148-1200, 22148-1620, 22148-2020, 22148-2110, 22148-2120, 22148-2130, 22148-2140, 22148-2150, 22148-2160, 22148-2280, 22148-2329, 22148-2410, 22148-2420, 22148-2430, 22148-2440, 22148-2450, 22148-2460, 22148-2470, 22148-2480, 22148-2490, 22148-2590, 22148-2710, 22148-2720, 22148-2730, 22148-2740, 22148-2750, 22148-2760, 22148-2770, 22148-2780, 22148-2790, 22148-2809, 22148-3010, 22148-3040, 22148-3060, 22148-3170, 22148-3240, 22148-3350, 22148-3510, 22148-3610, 22148-3680, 22148-3700, 22148-3710, 22148-3720, 22148-3730, 22148-3760, 22148-3780, 22148-3790, 22148-4040, 22148-4070, 22148-4110, 22148-4120, 22148-4260, 22148-4510, 22148-4700, 22148-4960, 22148-5040, 22148-5080, 22148-5110, 22148-5160, 22148-5230, 22148-5380, 22148-5450, 22148-5480, 22148-5760, 22148-5770, 22148-5820, 22148-6000, 22148-6030, 22148-6510, 22148-7030, 22148-7040, 22148-7070, 22148-7080, 22148-7150, 22148-7170, 22148-7230, 22148-7250, 22148-7330, 22148-7400, 22148-7480, 22148-7630, 22148-7910, 22148-8030, 22148-8080, 22148-8090, 22148-8110, 22148-8120, 22148-8230, 22148-8300, 22148-8340, 22148-8380, 22148-8430, 22148-8540, 22148-8710, 22148-8910

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 4 of 9

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat or drink.

Eye/face protection

Suitable eye protection: goggles.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	several
Odour:	solvent-like
pH-Value:	3 - 9 (25 ...)
Changes in the physical state	
Melting point:	not determined
Initial boiling point and boiling range:	> 82 °C
Flash point:	< 12 °C
Flammability	
Solid:	not applicable
Gas:	not applicable
Explosive properties	
not Explosive.	

Revision No. 1.00

Print date: 12.04.2018

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 5 of 9

Lower explosion limits:	1,8 vol. %
Upper explosion limits:	13,1 vol. %
Auto-ignition temperature	
Solid:	not applicable
Gas:	not applicable
Decomposition temperature:	not determined
Oxidizing properties	
Not oxidizing.	
Vapour pressure:	not determined
Vapour pressure: (at 50 °C)	60 hPa
Density:	1 g/cm ³
Water solubility:	easily soluble
Solubility in other solvents	
not determined	
Partition coefficient:	not determined
Vapour density:	not determined
Evaporation rate:	not determined
Solvent content:	75,02 %
9.2. Other information	
Solid content:	not determined

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Revision No: 1.00

Print date: 12.04.2018

Item Numbers: 22148-0000, 22148-1006, 22148-1012, 22148-1024, 22148-1048, 22148-1096, 22148-1120, 22148-1130, 22148-1200, 22148-1620, 22148-2020, 22148-2110, 22148-2120, 22148-2130, 22148-2140, 22148-2150, 22148-2160, 22148-2280, 22148-2329, 22148-2410, 22148-2420, 22148-2430, 22148-2440, 22148-2450, 22148-2460, 22148-2470, 22148-2480, 22148-2490, 22148-2590, 22148-2710, 22148-2720, 22148-2730, 22148-2740, 22148-2750, 22148-2760, 22148-2770, 22148-2780, 22148-2790, 22148-2809, 22148-3010, 22148-3040, 22148-3060, 22148-3170, 22148-3240, 22148-3350, 22148-3510, 22148-3610, 22148-3680, 22148-3700, 22148-3710, 22148-3720, 22148-3730, 22148-3760, 22148-3780, 22148-3790, 22148-4040, 22148-4070, 22148-4110, 22148-4120, 22148-4260, 22148-4510, 22148-4700, 22148-4960, 22148-5040, 22148-5080, 22148-5110, 22148-5160, 22148-5230, 22148-5380, 22148-5450, 22148-5480, 22148-5760, 22148-5770, 22148-5820, 22148-6000, 22148-6030, 22148-6510, 22148-7030, 22148-7040, 22148-7070, 22148-7080, 22148-7150, 22148-7170, 22148-7230, 22148-7250, 22148-7330, 22148-7400, 22148-7480, 22148-7630, 22148-7910, 22148-8030, 22148-8080, 22148-8090, 22148-8110, 22148-8120, 22148-8230, 22148-8300, 22148-8340, 22148-8380, 22148-8430, 22148-8540, 22148-8710, 22148-8910

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 6 of 9

Acute toxicity

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether					
	oral	LD50 mg/kg	> 5000	Ratte	IUCLID	
	dermal	LD50 mg/kg	11000	Kaninchen		

SECTION 12: Ecological Information

12.1. Toxicity

The product is not: Ecotoxic.

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether						
	Acute fish toxicity	LC50 10000 mg/l	4600 -	96 h	Leuciscus idus	IUCLID	
	Acute algae toxicity	ErC50 mg/l	> 1000	72 h	Selenastrum capricornutum		
	Acute crustacea toxicity	EC50 mg/l	> 500	48 h	Daphnia magna	IUCLID	

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-98-2	1-methoxy-2-propanol; monopropylene glycol methyl ether	-0,437

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The product has not been tested.

12.6. Other adverse effects

No information available.

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport Information

Land transport (ADR/RID)

Revision No. 1.00

Print date 12.04.2018

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 7 of 9

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Classification code: F1
Special Provisions: 274 601 640D
Limited quantity: 1 L
Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Special Provisions: 274
Limited quantity: 1 L
Excepted quantity: E2
EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (1-METHOXY-2-PROPANOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3
Special Provisions: A3
Limited quantity Passenger: 1 L
Passenger LQ: Y341
Excepted quantity: E2
IATA-packing instructions - Passenger: 353
IATA-max. quantity - Passenger: 5 L
IATA-packing instructions - Cargo: 364
IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

Revision No: 1,00

Print date: 12.04.2018

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)	Page 8 of 9
Revision date: 12.04.2018	

14.6. Special precautions for user

Warning: Combustible liquid.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 30a: 2-methoxypropanol

2010/75/EU (VOC): 75,174 % (751,738 g/l)

2004/42/EC (VOC): 75,174 % (751,738 g/l)

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Water contaminating class (D): 1 - slightly water contaminating

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

Highly flammable liquid and vapour.

Flammable liquid and vapour.

Causes skin irritation.

Causes serious eye damage.

Causes serious eye irritation.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May damage the unborn child.

Further Information

The information is based on present level of our knowledge. It does not, however, give assurances of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

Revision No: 1,00

Print date: 12.04.2018

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Blick Studio Art Marker Ink (all colors)

Revision date: 12.04.2018

Page 9 of 9

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Revision No: 1,00

Print date: 12.04.2018

Item Numbers: 22148-0000, 22148-1006, 22148-1012, 22148-1024, 22148-1048, 22148-1096, 22148-1120, 22148-1130, 22148-1200, 22148-1620, 22148-2020, 22148-2110, 22148-2120, 22148-2130, 22148-2140, 22148-2150, 22148-2160, 22148-2280, 22148-2329, 22148-2410, 22148-2420, 22148-2430, 22148-2440, 22148-2450, 22148-2460, 22148-2470, 22148-2480, 22148-2490, 22148-2590, 22148-2710, 22148-2720, 22148-2730, 22148-2740, 22148-2750, 22148-2760, 22148-2770, 22148-2780, 22148-2790, 22148-2809, 22148-3010, 22148-3040, 22148-3060, 22148-3170, 22148-3240, 22148-3350, 22148-3510, 22148-3610, 22148-3680, 22148-3700, 22148-3710, 22148-3720, 22148-3730, 22148-3760, 22148-3780, 22148-3790, 22148-4040, 22148-4070, 22148-4110, 22148-4120, 22148-4260, 22148-4510, 22148-4700, 22148-4960, 22148-5040, 22148-5080, 22148-5110, 22148-5160, 22148-5230, 22148-5380, 22148-5450, 22148-5480, 22148-5760, 22148-5770, 22148-5820, 22148-6000, 22148-6030, 22148-6510, 22148-7030, 22148-7040, 22148-7070, 22148-7080, 22148-7150, 22148-7170, 22148-7230, 22148-7250, 22148-7330, 22148-7400, 22148-7480, 22148-7630, 22148-7910, 22148-8030, 22148-8080, 22148-8090, 22148-8110, 22148-8120, 22148-8230, 22148-8300, 22148-8340, 22148-8380, 22148-8430, 22148-8540, 22148-8710, 22148-8910