

DENNISON MFG. COMPANY,STATIONARY PRODUCTS -- 3610 CARTER'S RUBBER CEMENT --  
6675-00-641-3610

=====  
Product Identification  
=====

Product ID:3610 CARTER'S RUBBER CEMENT  
MSDS Date:07/19/1988  
FSC:6675  
NIIN:00-641-3610  
MSDS Number: BGWSH  
=== Responsible Party ===  
Company Name:DENNISON MFG. COMPANY,STATIONARY PRODUCTS  
Address:300 HOWARD ST  
City:FRAMINGHAM  
State:MA  
ZIP:01701  
Country:US  
Info Phone Num:508-879-0511 X 4636  
Emergency Phone Num:508-879-0511 X 4636  
CAGE:FO467

==== Contractor Identification ===

Company Name:DENNISON MFG CO FASTENER DIVISION  
Address:300 HOWARD STREET  
Box:City:FRAMINGHAM  
State:MA  
ZIP:01701  
Country:US  
Phone:508-879-0511  
CAGE:5U802  
Company Name:DENNISON MFG. COMPANY CARTER'S INK DIV.  
Address:300 HOWARD STREET  
City:FRAMINGHAM  
State:MA  
ZIP:01701-8313  
Phone:(617) 879-0511  
CAGE:FO467  
Company Name:PACIFIC ENGINEERING AND INDUSTRIAL SUPPLY INC  
Address:840 W 1700 S  
Box:City:SALT LAKE CITY  
State:UT  
ZIP:84104-1735  
Country:US  
Phone:801-974-5940  
CAGE:1FJ69

=====  
Composition/Information on Ingredients  
=====

Ingred Name:SOLVENT NAPHTA  
CAS:64742-89-8  
Fraction by Wt: 88.6%  
OSHA PEL:400PPM  
ACGIH TLV:300PPM

=====  
Hazards Identification  
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:SEE SIGNS AND SYMPTOMS OF  
OVEREXPOSURE.  
Effects of Overexposure:CENTRAL NERVOUS SYSTEM DEPRESSION PRODUCING  
HEADACHES,DIZZINESS,NAUSEA, AND LOSS OF CONSCIOUSNESS.  
Medical Cond Aggravated by Exposure:INDIVIDUALS WITH A HISTORY OF  
RESPIRATORY OR SKIN DISEASES MAY BE AT INCREASED RISK FROM  
EXPOSURE.

=====  
===== First Aid Measures =====

First Aid: EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES. SEE DOCTOR.  
SKIN: REMOVE CONTAMINATED CLOTHING AND SHOES. WASH WITH SOAP AND WATER. SEE DOCTOR. INHALATION: REMOVE VICTIM TO FRESH AIR. GIVE OXYGEN/CPR IF NEEDED. SEE DOCTOR. INGESTION: GIVE LARGE QUANTITIES OF WATER OR MILK IF CONSCIOUS. DO NOT INDUCE VOMIT. SEE DOCTOR IMMEDIATELY. NOTHING BY MOUTH IF UNCONSCIOUS.

=====  
===== Fire Fighting Measures =====

Flash Point Method: TCC  
Flash Point: <10F, <-12C  
Lower Limits: 1.1  
Upper Limits: 7.0  
Extinguishing Media: ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.  
Fire Fighting Procedures: WEAR SCBA WITH A FULL FACE PIECE OPERATED IN PRESSURE-DEMAND MODE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS AND TO DISPERSE UNIGNITED VAPORS.  
Unusual Fire/Explosion Hazard: VAPORS HEAVIER THAN AIR. CAN TRAVEL A LONG DISTANCE ALONG GROUND AND FLASHBACK. CONTAINERS MAY EXPLODE IN HEAT OF FIRE.

=====  
===== Accidental Release Measures =====

Spill Release Procedures: CONTACT YOUR LOCAL ENVIRONMENTAL OFFICER. WEAR PROTECTIVE CLOTHING & EQUIPMENT. EVACUATE PERSONNEL. ELIMINATE IGNITION SOURCES. VENTILATE AREA. USE NON-SPARKING TOOLS. STOP LEAK. ABSORB IN INERT ABSORBENT & PLACE INTO APPROPRIATE DISPOSAL CONTAINER & SEAL.

=====  
===== Handling and Storage =====

Handling and Storage Precautions: STORE IN COOL, DRY, WELL VENTILATED PLACE, AWAY FROM HEAT, IGNITION SOURCES AND INCOMPATIBLE MATERIALS. KEEP CONTAINERS CLOSED WHEN NOT IN USE.  
Other Precautions: BOND AND GROUND CONTAINERS. NO SMOKING IN AREA.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH/MSHA RESPIRATOR WITH CARTRIDGE APPROPRIATE FOR EXPOSURE OF CONCERN OR SCBA IF TLV IS EXCEEDED.  
Ventilation: SUFFICIENT MECHANICAL (GENERAL) AND/OR LOCAL EXHAUST VENTILATION TO MAINTAIN EXPOSURE BELOW TLV.  
Protective Gloves: PVA, NITRILE.  
Eye Protection: SAFETY GLASSES W/SIDE SHIELDS.  
Other Protective Equipment: FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED SKIN CONTACT. EYE WASH STATION AND SAFETY SHOWER.  
Work Hygienic Practices: AVOID CONTACT WITH EYES & SKIN. DO NOT BREATHE VAPORS. WASH THOROUGHLY AFTER HANDLING. LAUNDRY CONTAMINATED CLOTHING.  
Supplemental Safety and Health  
NONE.

=====  
===== Physical/Chemical Properties =====

HCC: F2  
Boiling Pt: B.P. Text: 151-225F  
Vapor Pres: 250  
Vapor Density: 3.3  
Spec Gravity: 0.72

Evaporation Rate & Reference:5.8 (BUTYL ACETATE=1)  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:BUFF COLOR LIQUID WITH HYDROCARBON ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS LIKE CHLORINE.  
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAMES.  
Hazardous Decomposition Products:DURING COMBUSTION MAY FORM CARBON  
MONOXIDE, CARBON DIOXIDE, UNIDENTIFIED CARBON PRODUCTS.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS PENDING DISPOSAL.CONTACT  
YOUR LOCAL ENVIRONMENTAL OFFICER FOR DISPOSAL.DISPOSE OF IN  
ACCORDANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL  
ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.